
DS-RVPW014-RBE-017-2412-1

6W ◊ Regulated Isolated Output ◊ 4:1 Input

RECOM
DC/DC Converter

FEATURES

- Wide input range (9V - 36V)
- Isolation voltage 3kVDC/min
- Primary side regulation
- Operating temperature: -40°C to +85°C
- Short circuit protection
- Castellated connections



Dimensions (LxWxH): 43.18 x 25.4 x 6.0mm (1.7 x 1.0 x 0.24 inch)
4.95g (0.011lbs)

DESCRIPTION

This application scheme is based on a highly integrated peak current type flyback power supply controller RVPW014, combined with an isolated power transformer RBE-017, output rectifier diode, and necessary resistive and capacitive components, to achieve a 9V-36V input, 12V output isolated voltage stabilizing power supply solution. This scheme can achieve the maximum output power of 6W within the full input voltage range, with the primary and secondary isolation withstand voltage not less than 3000VDC. It also features remote control shutdown, long-term short-circuit protection and self-recovery functions. This scheme can be applied in scenarios where electrical isolation is required on the system board to achieve safety and/or anti-interference purposes.

SELECTION GUIDE

Part Number	Input Voltage Range [VDC]	Output Voltage [VDC]	Output Current max. [mA]	Efficiency typ. [%]	max. Capacitive[1] [µF]
DS-RVPW014-RBE-017-2412-1	9-36	12	500	85	1000

Note 1: Max. capacitive load is tested at nominal input voltage and full load


BASIC CHARACTERISTIC (measured @ T_{AMB}= 25°C, nominal Input and full load after warm-up time unless otherwise noted)

Parameter	Condition	Min.	Typ.	Max.
Input Voltage Range		9VDC	24VDC	36VDC
Minimum Load		0%		
Internal Operating Frequency			330kHz	
Output Ripple and Noise	20MHz BW			100mVp-p


copyright © RECOM Power GmbH, all rights reserved
www.recom-power.com

SPECIFICATIONS (measured @ T_{AMB}= 25°C, nominal Input and full load after warm-up time unless otherwise noted)

Typical Effiency vs. Output Current Curve




Typical Effiency vs. Inutput Voltage Curve




Typical Waveform

V_{IN} =24V, Full-load output voltage ripple waveform



V_{IN} =24V, Full load startup waveform



REGULATIONS

Parameter	Condition	Values
Output Accuracy		±2.0% Typ.
Line Regulation	low line to high line, full load	±3.0% Typ.
Load Regulation	10% to 100% load, V_{OUT}	±2.0% Typ.

PROTECTION AND ISOLATION CAPABILITIES

Short Circuit Protection		continuous, automatic recovery
Isolation Voltage	tested for 1 minute	3kVDC min.
Insulation Grade		functional

copyright © RECOM Power GmbH, all rights reserved
www.recom-power.com

DS-RVPW014-RBE-017-2412-1

6W ◊ Regulated Isolated Output ◊ 4:1 Input


RECOM DC/DC Converter

ENVIRONMENT

Parameter	Condition	Values
Operating Temperature Range	full load	-40°C to +85°C

Derating Graph

(@ Chamber and natural convection 0.1m/s)




DIMENSION & PHYSICAL CHARACTERISTICS

Parameter	Type	Values
Material	PCB	FR4, (UL94 V-0)
Dimension (LxWxH)		43.18 x 25.4 x 7.0 mm
Weight		4.95g typ. (0.011 lbs)

Dimension Drawing (mm)

Pinning Information	
Pin #	Single
1,2,3	V_{IN}
7,8,9	GND
10,11,12	V_{OUT-}
16,17,18	V_{OUT+}




copyright © RECOM Power GmbH, all rights reserved
www.recom-power.com

DS-RVPW014-RBE-017-2412-1

6W ◊ Regulated Isolated Output ◊ 4:1 Input

RECOM DC/DC Converter

SCHEMATIC



BOM

Component Designator	Description	Package	Manufacturer Part Number	Manufacturer
C1	4.7uF/50V-X7R	1206	CC1206KKX7R9BB475	YAGEO
C2	1uF/25V-X7R	0603	CC0603KRX7R8BB105	YAGEO
C3	100nF/50V-X7R	0603	CC0603KRX7R9BB104	YAGEO
C4,C5,C6	22uF/16V-X5R	1206	CC1206KKX5R7BB226	YAGEO
C8	100pF/200V-NPO	0805	CC0805JRNPOABN101	YAGEO
C7,C9,C10	NC	-	-	-
Y1	1nF/3KV-X7R	1808	CC1808KKX7REBB102	YAGEO
R1	470KΩ±1%	0603	RC0603FR-07470KL	YAGEO
R2	150KΩ±1%	0603	RC0603FR-07150KL	YAGEO
R3	680KΩ±1%	0603	RC0603FR-07680KL	YAGEO
R4	27KΩ±1%	0603	RC0603FR-0727KL	YAGEO
R5	5.1KΩ±1%	0603	RC0603FR-075K1L	YAGEO
R6	22KΩ±1%	0603	RC0603FR-0722KL	YAGEO
R7	10KΩ±1%	0603	RC0603FR-0710KL	YAGEO
R8	1KΩ±1%	0603	RC0603FR-071KL	YAGEO
R9	2.4KΩ±1%	1206	RC1206FR-072K4L	YAGEO
R10	10Ω±1%	0805	RC0805FR-0710RL	YAGEO
R11,R12,R13,R14,R15,R16	-	-	-	-
TR1	-	ER11.5	RBE-017	RECOM
D1,D2	200V/0.2A	SOD-323	BAV21WS	CJ
D3	100V/2A	SMA	SS210A	YANGJIE
U1	-	ESOP-8	RVPW014	RECOM
U2,U3	NC	-	-	-

The product information and specifications may be subject to changes even without prior written notice.The product has been designed for various applications; its suitability lies in the responsibility of each customer. The products are not authorized for use in safety-critical applications without RECOM's explicit written consent. A safety-critical application is an application where a failure may reasonably be expected to endanger or cause loss of life, inflict bodily harm or damage property. The applicant shall indemnify and hold harmless RECOM, its affiliated companies and its representatives against any damage claims in connection with the unauthorized use of RECOM products in such safety-critical applications.

copyright © RECOM Power GmbH, all rights reserved
www.recom-power.com